

TATUNG V37MCGISense the ultimate....The Tatung 37" integrated HD Widescreen LCD TV

Features

- •Comply Europe PAL/SECAM system, B/G, D/K, I, L/L'
- •Compatible with all 576i/576p/720p/1080i video formats
- •Universal video color system, PAL / SECAM / NTSC
- •Progressive Scan, 2:2 Pull Down
- •3D de-interlacer & Comb Filter
- •Auto Program System & Searching (APS)
- •Auto Volume & Power Control
- •Teletext 100 pages

System Spec.

•Resolution: 1366 x 768

•Brightness: 550 cd/m2

•Contrast Ratio: 1000:1

•HDMI/DVI Connectivity

•Response Time: 8 ms



TATUNG 37" integrated HD Widescreen LCD TV Product Specification

Items	Model Name	V37MCGI (EU Model)
Panel	Screen Size	37.0" TFT-LCD Panel (CPT)
	Aspect Ratio	16:9
	Resolution	1366 x 768
	Display Area (opening) H x V	819.6 mm x 460.8 mm
	Pixel Pitch	0.6 mm x 0.6 mm
	Display colors	16,777,216 colors
	Contrast Ratio	1000:1 (typ.)
	Brightness (center)	550 cd / m2 (typ.)
	Viewing Angle (CR>10)	170° Hor. / 170° Ver. (typ.)
	Response Time (BTW)	8 ms (typ.)
TV function	Broadcasting System	Analog : PAL / SECAM
	Receiving Channel	Analog:B/G,D/K,I and L/L'
	Sound System	Analog : NICAM / A2 (IGR)
	Resolution	Analog: 625i
	Data Broadcasting	Teletext 100 pages (FLOF /TOP), Auto Program Searching (APS)
Video Input	Video Color System	PAL / SECAM / NTSC
	AV1 (SCART)	21-pin Scart (RGB / CVBS) x 1
	AV2 (SCART)	21-pin Scart (RGB / CVBS/ SVHS) x 1
	AV3 (CVBS, Y/C)	Composite (RCA jack) x 1
		S-Video x 1
	AV4 (Component)	Y Pb Pr (720p / 1080i , HDTV ready) x 1
	AV5 (HDMI)	HDMI 19 pin x 1 (HDMI 1.1 / HDCP 1.1)
PC Input (analog)	DVI-D Connection	DVI-D x 1
	VGA Connection	D-Sub 15 pin x 1
	Scanning Frequency	f _H = 31.5 ~ 60KHz / f _V = 56 ~ 75Hz
Audio Input	Audio 1	SCART (build-in) x 2
	Audio 2	Composite x 1
		S - Video x 1
		Component x1
	Audio 3	PC x 1
Video Output	SCART 1	TV / CVBS/ S-Video
	SCART 2	TV / CVBS / S-Video
	Composite (RCA jack)	TV / CVBS / S-Video/SCART1/SCART2
Audio Out	Speaker (build-in)	15W +15W (rms) @ THD < 10%
	Line Out	Left / Right / Subwoofer
	SP/DIF (Optic)	All source (*Dolby AC3, PCM, MPEG from Digital TV is optional)
Feature	OSD Language	English, French, German, Spanish, Italian, Finnish, Swedish, Dutch, Demark, Norwa
	Function Keys	Power , Source , Menu , Up/Down(Channel) , +/-(Volume) , ARC/EXIT .
	Video Performance	3D Comb-filter, 3D De-interlace, Advanced Chroma Processing,
		Video Enhance, Noise Reduction, 2-2 Pull Down
	Audio Performance	Equalizer, Subwoofer, Auto Volume Control (AVC),
	Other Control	PIP, Canal+, Auto Progress System (APS), Aspect Ratio Control (ARC),
		Auto Picture Control (APC), Auto Sleep Timer, Auto Power On
Power	Power supply	AC 100V ~ 240V ,50 / 60Hz
	Power Consumption	220 W
Dimensions	WxHxD	1111.3mm x 632.3mm x 279.7mm
Weight (Net)	Without Accessories	26.5 kg

^{*}Product specification and design are subject to change without notice.